

New Bridge Services pty ltd
Manufactures OF QUALITY PRODUCTS
ACN: 122862355

NBS VET CATTLE CRUSHER MAINTENANCE MANUAL

Installation:

NBS vet cattle crusher should be bolted to a concrete Foundation or slab with dyna Bolts using the fixing plate that are provided for better stability of the crush .Kindly avoid contact with stagnated water/soil although the crushers are HDG after fabrication it can reduce and damage/Corrode the HDG finish.

Maintenance:

1. After every use the crusher should be washed down with a high pressure hose
2. All moving parts /latches/Springs/ hinges to be lubricated to avoid corrosion/ rusting
3. Before every use all bolts and levers to be checked and tightened if loose, worn out bolts to be Replaced if necessary

Only Authorised and qualified operators should only be allowed to work on the crush, New Bridge Services Pty Ltd takes no responsibility for any injury /damage/breakage caused due to misuse and not following the operation/Installation/maintenance procedures of our product.

We offer a 1 Year Warranty on workmanship on our Crusher based on the above Procedures/Installation and Maintenance is followed. Any modification or accessories used in conjunction that are not supplied/ installed by New Bridge Services Pty Ltd will void the warranty.

New Bridge Services Pty Ltd reserves the right to change or modify its products with our prior notice.

TERMS & CONDITIONS

- 1) The product is designed to suit its applications, and will always be supplied in standard panel widths Unless mentioned.
- 2) All goods are subject to be inspect of the buyer prior or during acceptance of deliver, no claims of Damage/defects will be entertained thereafter.
- 4) All care will be taken in supplying your order, however if error occur, new bridge services reserve the right to make good the defective Material. No claim for repair or replacement will be recognized unless first agreed in writing by new bridge services.
- 5) New bridge considers that the customer is familiar with the procedures and tolerances noted in the New bridge catalogue.
- 6) It is the sole Responsibility of the installer to observe and ensure the guide lines of erecting on site. New bridge services pty ltd takes no Responsibility for any damage to public/ persons / Property Caused by the installer/ operator .
- 7) All warranty is covered with an original Invoice and is not transferable, installation and dismantling Charges are not covered under this warranty.

5 Fernwren Drive, Berwick VIC 3806 .

PHONE: +61 3 97026078, MOBILE: +61 (0) 437911195, FAX: +61 3 97022095

Web:newbridgeservices.com.au

Email : sales@newbridgeservices.com.au