



Model	NB-7120HURB	
Certificate	CCC, CE, Rosh	
Shell material	Steel	
Moisture capacity (30°C,80%RH)	120L/D	138L/D
Voltage / Cycle	110-130V/50Hz/60HZ; 220-240V/50HZ	
Plug	UK /EEC/America/Japan/South Africa/ Australia/ standard	
Power input (W)	1650	1750
Current A	7.5	8
Noise Level	Less than 59 decibel	
Fan speed	1	
Air flow m³/h	1050	1100
Air filter	<b>Nylon Filter</b>	
Cryogen/refrigerant gas	R407c (client requirement)	
Applied area (2.6 high) sq.m.	150-200	160-250
Operating Temp. Range °C	5-38	
Control type	Micro-computer	
Control panel	Color LED display	
Sensor	Humidity sensor	
Compressor	Rotary	
Safety	3 minutes delayed for protecting	
Timer	1-24h	
Power off memory function	yes	
Auto defrost	Yes	
Body dimension (mm) L*W*H	400*410*1000	
Packing dimension (mm)L*W*H	500*500*1200	
Tank capacity (L)	Water pipe	
Maneuverability	4 casters	
N/W (Kg)	48	50
G/W (Kg)	53	54.5
Qty 20'GP units	Qty 40'GP units	
80	160	
Payment term	TT,	